



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 25.11.2022

Version number 5 (replaces version 3)

Revision: 25.11.2022

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· Trade name: **Signum metal bond I**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.

· **Application of the substance / the mixture** Metal-Resin Bonding System

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

· **Informing department:** E-Mail: [msds@kulzer-dental.com](mailto:msds@kulzer-dental.com)

· **1.4 Emergency telephone number:** Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

**SECTION 2: Hazards identification**

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**

acetone

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves / eye protection.

P337+P313 If eye irritation persists: Get medical advice/attention.

· **2.3 Other hazards -**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

GB

(Contd. on page 2)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 25.11.2022

Version number 5 (replaces version 3)

Revision: 25.11.2022

**Trade name: Signum metal bond I**

(Contd. of page 1)

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Description:** -

**Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	>90%
CAS: 85590-00-7 EC number: 874-929-2	10-(Phosphonooxy)decyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	0-5%
CAS: 64-19-7 EINECS: 200-580-7 Reg.nr.: 01-2119475328-30-XXXX	acetic acid Flam. Liq. 3, H226 Skin Corr. 1A, H314; Eye Dam. 1, H318 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 90% Skin Corr. 1B; H314: 25 % ≤ C < 90 % Skin Irrit. 2; H315: 10 % ≤ C < 25 % Eye Irrit. 2; H319: 10 % ≤ C < 25 %	≥1-<3%

**Additional information** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**After inhalation** Supply fresh air; consult doctor in case of symptoms.

**After skin contact**

Instantly rinse with water.

If skin irritation continues, consult a doctor.

**After eye contact**

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

**After swallowing**

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing agents**

CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

**For safety reasons unsuitable extinguishing agents** Water with a full water jet.

**5.2 Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

**5.3 Advice for firefighters**

**Protective equipment:**

Wear self-contained breathing apparatus.

Wear full protective suit.

(Contd. on page 3)



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 25.11.2022

Version number 5 (replaces version 3)

Revision: 25.11.2022

**Trade name: Signum metal bond I**

· **Additional information -**

(Contd. of page 2)

**SECTION 6: Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Avoid contact with eyes and skin.

Use breathing protection against the effects of fumes/dust/aerosol.

· **6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars.**

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

Ensure adequate ventilation.

Send for recovery or disposal in suitable containers.

· **6.4 Reference to other sections**

See Section 13 for information on disposal.

See Section 8 for information on personal protection equipment.

-

**SECTION 7: Handling and storage**

· **7.1 Precautions for safe handling**

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and containers: Store in cool location.**

· **Information about storage in one common storage facility: Not required.**

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed containers.

· **7.3 Specific end use(s) No further relevant information available.**

**SECTION 8: Exposure controls/personal protection**

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

**67-64-1 acetone**

WEL (Great Britain)

Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm

Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

IOELV (European Union)

Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

**64-19-7 acetic acid**

WEL (Great Britain)

Short-term value: 50 mg/m<sup>3</sup>, 20 ppm

Long-term value: 25 mg/m<sup>3</sup>, 10 ppm

IOELV (European Union)

Short-term value: 50 mg/m<sup>3</sup>, 20 ppm

Long-term value: 25 mg/m<sup>3</sup>, 10 ppm

(Contd. on page 4)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 25.11.2022

Version number 5 (replaces version 3)

Revision: 25.11.2022

**Trade name: Signum metal bond I**

(Contd. of page 3)

· **DNELs**

**67-64-1 acetone**

Oral	general population, long term, systemic	62 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	186 mg/Kg/d (not defined)
	general population, long term, systemic	62 mg/Kg/d (not defined)
Inhalative	worker industrial, long term, systemic	1,210 mg/m3 (not defined)
	worker industrial, long term, local	2,420 mg/m3 (not defined)
	general population, long term, systemic	200 mg/m3 (not defined)

· **PNECs**

**67-64-1 acetone**

freshwater	10.6 mg/l (not defined)
marine water	1.06 mg/l (rabbit)
sewage treatment plant	19.5 mg/l (not defined)
sediment, dry weight, freshwater	30.4 mg/Kg (not defined)
sediment, dry weight, marine water	3.04 mg/Kg (not defined)
soil, dry weight	0.112 mg/Kg (not defined)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Avoid contact with the eyes.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

Filter AX.

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

· **Hand protection**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition.  
recommended

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Butyl rubber, BR

Nitrile rubber, NBR

· **Eye/face protection** Tightly sealed safety glasses.

(Contd. on page 5)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 25.11.2022

Version number 5 (replaces version 3)

Revision: 25.11.2022

**Trade name: Signum metal bond I**

(Contd. of page 4)

- **Body protection:**  
Protective work clothing.  
Light weight protective clothing

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

- **Physical state** Fluid
- **Colour:** Colourless
- **Smell:** Acetone-like
  - **Odour threshold:** Not determined.
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range** 55 °C
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
  - **Lower:** 2.6 Vol %
  - **Upper:** 13.0 Vol %
- **Flash point:** -17 °C (67-64-1 acetone)
- **Ignition temperature:** 465 °C (67-64-1 acetone)
- **Decomposition temperature:** Not determined.

· **SADT**

- **pH at 20 °C** 5-6
- **Viscosity:**
  - **Kinematic viscosity** Not determined.
  - **dynamic:** Not determined.
- **Solubility**
  - **Water:** Not miscible or difficult to mix
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Steam pressure at 20 °C:** 247 hPa
- **Density and/or relative density**
  - **Density** Not determined
  - **Relative density** Not determined.
  - **Vapour density** Not determined.

· **9.2 Other information**

No further relevant information available.

· **Appearance:**

- **Form:** Fluid

· **Important information on protection of health and environment, and on safety.**

- **Self-inflammability:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures is possible.

· **Change in condition**

- **Evaporation rate** Not determined.

· **Information with regard to physical hazard classes**

- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void

(Contd. on page 6)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 25.11.2022

Version number 5 (replaces version 3)

Revision: 25.11.2022

**Trade name: Signum metal bond I**

(Contd. of page 5)

· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Highly flammable liquid and vapour.
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
  - **Conditions to be avoided:** No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** None
- **Additional information:** -

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
  - **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

**67-64-1 acetone**

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	>15,800 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (rat)

**64-19-7 acetic acid**

Oral	LD50	3,310 mg/kg (rat)
Inhalative	LC50/4 h	11.4 mg/l (rat) (OECD 403)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 7)



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 25.11.2022

Version number 5 (replaces version 3)

Revision: 25.11.2022

**Trade name: Signum metal bond I**

(Contd. of page 6)

· **Subacute to chronic toxicity:**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**67-64-1 acetone**

EC50/48h 8,800 mg/l (daphnia)

LC50/96h 6,210 mg/l (fish) (OECD 203)

**64-19-7 acetic acid**

EC50/48h >300.82 mg/l (daphnia) (OECD 202)

LC50/96h >1,000 mg/l (fish) (OECD 203)

ErC50 / 72 h >1,000 mg/l (algae)

NOEC / 72h 1,000 mg/l (algae)

NOEC / 96h 1,000 mg/l (fish) (OECD 203)

· **12.2 Persistence and degradability**

**67-64-1 acetone**

Biodegradation 90.9 % /28d (not defined) (OECD 301D)

**64-19-7 acetic acid**

Biodegradation 96 % /20d (not defined)

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· **Uncleaned packagings:**

· **Recommendation:**

Disposal must be made according to official regulations.

Non contaminated packagings can be used for recycling.

GB

(Contd. on page 8)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 25.11.2022



Version number 5 (replaces version 3)

Revision: 25.11.2022

**Trade name: Signum metal bond I**

(Contd. of page 7)

**SECTION 14: Transport information**

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1090
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1090 ACETONE solution ACETONE solution
· 14.3 Transport hazard class(es) · ADR	
	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category	Warning: Flammable liquids. 33 F-E,S-D E
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	-
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging:

(Contd. on page 9)





**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 25.11.2022

Version number 5 (replaces version 3)

Revision: 25.11.2022

**Trade name: Signum metal bond I**

(Contd. of page 8)

500 ml

· **UN "Model Regulation":**

UN 1090 ACETONE SOLUTION, 3, II

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t**

· **Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t**

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Abbreviations and acronyms:**

SADT: Self Accelerating Decomposition Temperature

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· **\* Data compared to the previous version altered.**



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 03.08.2022

Version number 5 (replaces version 4)

Revision: 03.08.2022

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· Trade name: **Signum metal bond II**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.

· Application of the substance / the mixture Metal-Resin Bonding System

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

· Informing department: E-Mail: [msds@kulzer-dental.com](mailto:msds@kulzer-dental.com)

· **1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463**

**SECTION 2: Hazards identification**

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS02 GHS07 GHS09

· **Signal word Danger**

· **Hazard-determining components of labelling:**

methyl methacrylate

7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

tert-butyl perbenzoate

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

(Contd. on page 2)

GB



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 03.08.2022

Version number 5 (replaces version 4)

Revision: 03.08.2022

**Trade name: Signum metal bond II**

(Contd. of page 1)

- **2.3 Other hazards -**
- **Results of PBT and vPvB assessment**
  - **PBT:** Not applicable.
  - **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

- **3.2 Mixtures**
- **Description: -**

· **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥50-≤75%
CAS: 72869-86-4 EINECS: 276-957-5 Reg.nr.: 01-2120751202-68-xxxx	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate Aquatic Chronic 2, H411 Skin Sens. 1B, H317 EUH204	≥10-<25%
CAS: 75980-60-8 EINECS: 278-355-8 Reg.nr.: 01-2119972295-29-xxxx	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide Repr. 2, H361f Aquatic Chronic 2, H411 Skin Sens. 1B, H317	≥1-<2.5%
CAS: 614-45-9 EINECS: 210-382-2	tert-butyl perbenzoate Org. Perox. C, H242 Aquatic Acute 1, H400 Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317 Aquatic Chronic 3, H412	≥0.1-<0.25%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
  - **After inhalation** Supply fresh air; consult doctor in case of symptoms.
  - **After skin contact**  
Instantly wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
  - **After eye contact**  
Rinse opened eye for several minutes under running water. Then consult doctor.
  - **After swallowing**  
Rinse out mouth and then drink plenty of water.  
In case of persistent symptoms consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

GB  
(Contd. on page 3)



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 03.08.2022

Version number 5 (replaces version 4)

Revision: 03.08.2022

**Trade name: Signum metal bond II**

(Contd. of page 2)

### **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
  - **Suitable extinguishing agents**  
CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- **5.2 Special hazards arising from the substance or mixture**  
Can form explosive gas-air mixtures.  
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
  - **Protective equipment:** Wear self-contained breathing apparatus.
  - **Additional information -**

### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Avoid contact with eyes and skin.
- **6.2 Environmental precautions:**  
Do not allow to enter drainage system, surface or ground water.  
Do not allow to enter the ground/soil.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).  
Send for recovery or disposal in suitable containers.
- **6.4 Reference to other sections**  
See Section 13 for information on disposal.  
See Section 8 for information on personal protection equipment.
- 

### **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Keep containers tightly sealed.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
  - **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
  - **Storage**
    - **Requirements to be met by storerooms and containers:** Store in cool location.
    - **Information about storage in one common storage facility:** Not required.
    - **Further information about storage conditions:**  
Store in cool, dry conditions in well sealed containers.
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 03.08.2022

Version number 5 (replaces version 4)

Revision: 03.08.2022

**Trade name: Signum metal bond II**

(Contd. of page 3)

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Components with critical values that require monitoring at the workplace:**

**80-62-6 methyl methacrylate**

WEL (Great Britain)	Short-term value: 416 mg/m <sup>3</sup> , 100 ppm Long-term value: 208 mg/m <sup>3</sup> , 50 ppm
IOELV (European Union)	Short-term value: 100 ppm Long-term value: 50 ppm

**DNELs**

**80-62-6 methyl methacrylate**

Oral	general population, long term, systemic	8.2 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	13.67 mg/Kg/d (not defined)
	general population, long term, systemic	8.2 mg/Kg/d (not defined)
Inhalative	worker industrial, acute, local	416 mg/m <sup>3</sup> (not defined)
	worker industrial, long term, systemic	348.4 mg/m <sup>3</sup> (not defined)
	worker industrial, long term, local	208 mg/m <sup>3</sup> (not defined)
	general population, acute, local	208 mg/m <sup>3</sup> (not defined)
	general population, long term, systemic	74.3 mg/m <sup>3</sup> (not defined)

**72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate**

Oral	general population, long term, systemic	0.3 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	1.3 mg/Kg/d (not defined)
	general population, long term, systemic	0.7 mg/Kg/d (not defined)
Inhalative	worker industrial, long term, systemic	3.3 mg/m <sup>3</sup> (not defined)
	general population, long term, systemic	0.6 mg/m <sup>3</sup> (not defined)

**75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide**

Oral	general population, long term, systemic	0.0833 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	0.233 mg/Kg/d (not defined)
	general population, long term, systemic	0.0833 mg/Kg/d (not defined)
Inhalative	worker industrial, long term, systemic	0.822 mg/m <sup>3</sup> (not defined)
	general population, long term, systemic	0.145 mg/m <sup>3</sup> (not defined)

**PNECs**

**80-62-6 methyl methacrylate**

freshwater	0.94 mg/l (not defined)
marine water	0.094 mg/l (not defined)
sewage treatment plant	10 mg/l (not defined)
sediment, dry weight, freshwater	10.2 mg/Kg (not defined)
sediment, dry weight, marine water	0.102 mg/Kg (not defined)
soil, dry weight	1.48 mg/Kg (not defined)

**72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate**

freshwater	0.01 mg/l (not defined)
marine water	0.001 mg/l (not defined)
sewage treatment plant	3.61 mg/l (not defined)

(Contd. on page 5)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 03.08.2022

Version number 5 (replaces version 4)

Revision: 03.08.2022

**Trade name: Signum metal bond II**

(Contd. of page 4)

sediment, dry weight, freshwater	4.56 mg/Kg (not defined)
sediment, dry weight, marine water	0.46 mg/Kg (not defined)
soil, dry weight	0.91 mg/Kg (not defined)
<b>75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide</b>	
freshwater	0.0014 mg/l (not defined)
marine water	0.00014 mg/l (not defined)
sediment, dry weight, freshwater	0.115 mg/Kg (not defined)
sediment, dry weight, marine water	0.0115 mg/Kg (not defined)
soil, dry weight	0.0222 mg/Kg (not defined)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

· **Hand protection**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Solvent resistant gloves

Check protective gloves prior to each use for their proper condition.  
recommended

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Butyl rubber, BR

Nitrile rubber, NBR

· **Eye/face protection** Safety glasses

· **Body protection:** Protective work clothing.

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

(Contd. on page 6)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 03.08.2022

Version number 5 (replaces version 4)

Revision: 03.08.2022

**Trade name: Signum metal bond II**

(Contd. of page 5)

· <b>Colour:</b>	White
· <b>Smell:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.
· <b>Melting point/freezing point:</b>	Not determined
· <b>Boiling point or initial boiling point and boiling range</b>	100 °C
· <b>Flammability</b>	Not applicable.
· <b>Lower and upper explosion limit</b>	
· <b>Lower:</b>	2.1 Vol %
· <b>Upper:</b>	12.5 Vol %
· <b>Flash point:</b>	10 °C (80-62-6 methyl methacrylate)
· <b>Ignition temperature:</b>	430 °C
· <b>Decomposition temperature:</b>	Not determined.

· **SAPT**

Signum metal bond II > 60 °C

· **SADT**

· <b>pH</b>	Mixture is non-soluble (in water).
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not determined.
· <b>dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>Water:</b>	Not miscible or difficult to mix
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Steam pressure at 20 °C:</b>	47 hPa
· <b>Density and/or relative density</b>	
· <b>Density</b>	Not determined
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.

· **9.2 Other information**

No further relevant information available.

· **Appearance:**

· **Form:**

Fluid

· **Important information on protection of health and environment, and on safety.**

· **Self-inflammability:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures is possible.

· **Change in condition**

· **Evaporation rate**

Not determined.

· **Information with regard to physical hazard classes**

· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Highly flammable liquid and vapour.
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void

(Contd. on page 7)



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 03.08.2022

Version number 5 (replaces version 4)

Revision: 03.08.2022

**Trade name: Signum metal bond II**

(Contd. of page 6)

- |  |      |
|--|------|
| · <b>Self-heating substances and mixtures</b>                                      | Void |
| · <b>Substances and mixtures, which emit flammable gases in contact with water</b> | Void |
| · <b>Oxidising liquids</b>   | Void |
| · <b>Oxidising solids</b>  | Void |
| · <b>Organic peroxides</b>   | Void |
| · <b>Corrosive to metals</b>   | Void |
| · <b>Desensitised explosives</b>   | Void |

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
  - **Conditions to be avoided:** No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** None
  - **Additional information:**  
If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
  - **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

**80-62-6 methyl methacrylate**

Oral	LD50	~7,900 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (guinea pig) (OECD 402)
Inhalative	LC50/4 h	29.8 mg/l (rat)

**72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate**

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

**75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide**

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

**614-45-9 tert-butyl perbenzoate**

Oral	LD0	2,000 mg/kg (rat) (OECD 423)
Dermal	LD0	2,000 mg/kg (rat) (OECD 402)
Inhalative	LC0/4h	1.01 mg/L (rat) (OECD 439)
	LC100/4h	4.9 mg/L (rat) (OECD 439)

- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 8)





**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 03.08.2022

Version number 5 (replaces version 4)

Revision: 03.08.2022

**Trade name: Signum metal bond II**

(Contd. of page 7)

- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**80-62-6 methyl methacrylate**

EC50/21d	49 mg/L (daphnia) (OECD 211)
EC50/48h	69 mg/l (daphnia) (EPA OTS 797.1300)
NOEC / 21d	37 mg/l (daphnia) (OECD 211)
ErC50 / 72 h	>110 mg/l (algae) (OECD 201)
NOEC / 72h	110 mg/l (algae) (OECD 201)
NOEC / 48h	48 mg/l (daphnia) (EPA OTS 797.1300)
EbC50 / 72h	>110 mg/l (algae) (OECD 201)
NOEC/ 35d	9.4 mg/L (fish) (OECD 210)
LC50/ 35d	33.7 mg/L (fish) (OECD 210)

**72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate**

EC50/48h	>1.2 mg/l (daphnia) (OECD 202)
LC50/96h	10.1 mg/l (fish) (OECD 203)
ErC50 / 72 h	>0.68 mg/l (algae) (OECD 201)
NOEC / 72h	0.21 mg/l (algae) (OECD 201)

**75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide**

EC50/48h	10,100 mg/l (algae)
	3.53 mg/l (daphnia) (OECD 202)
LC50/96h	1.4 mg/l (fish) (OECD 203)
ErC50 / 72 h	>2.01 mg/l (algae) (OECD 201)
ErC10/72h	1.56 mg/L (algae) (OECD 201)

· **12.2 Persistence and degradability**

**80-62-6 methyl methacrylate**

Biodegradation 94 % /14d (not defined) (OECD 301C)

**72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate**

Biodegradation 22 % /28d (not defined) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)

**75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide**

Biodegradation 0-10 % /28d (not defined) (OECD 301F; ISO 9408/ EEC 92/69/V, C.4-D)

(Contd. on page 9)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 03.08.2022

Version number 5 (replaces version 4)

Revision: 03.08.2022

**Trade name: Signum metal bond II**

(Contd. of page 8)

· **12.3 Bioaccumulative potential**

**75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide**

Bloconcentration factor (BCF) 47-55 (not defined)

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

**SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· **Uncleaned packagings:**

· **Recommendation:**

Disposal must be made according to official regulations.

Non contaminated packagings can be used for recycling.

**SECTION 14: Transport information**

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

UN1993

· **14.2 UN proper shipping name**

· **ADR**

1993 FLAMMABLE LIQUID, N.O.S., special provision 640D (METHYL METHACRYLATE MONOMER, STABILIZED)

· **IMDG**

FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED), MARINE POLLUTANT

· **IATA**

FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED)

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class**

3 (F1) Flammable liquids.

(Contd. on page 10)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**




Printing date 03.08.2022

Version number 5 (replaces version 4)

Revision: 03.08.2022

**Trade name: Signum metal bond II**

(Contd. of page 9)

· Label	3
· IMDG	
 	
· Class	3 Flammable liquids.
· Label	3
· IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Kemler Number:	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	-
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 11)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 03.08.2022

Version number 5 (replaces version 4)

Revision: 03.08.2022

**Trade name: Signum metal bond II**

(Contd. of page 10)

· **UN "Model Regulation":** UN 1993 FLAMMABLE LIQUID, N.O.S., SPECIAL PROVISION 640D (METHYL METHACRYLATE MONOMER, STABILIZED), 3, II

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
  - **Directive 2012/18/EU**
    - **Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t**
    - **Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t**
- **15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**

**SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
  - H225 Highly flammable liquid and vapour.
  - H242 Heating may cause a fire.
  - H315 Causes skin irritation.
  - H317 May cause an allergic skin reaction.
  - H332 Harmful if inhaled.
  - H335 May cause respiratory irritation.
  - H361f Suspected of damaging fertility.
  - H400 Very toxic to aquatic life.
  - H411 Toxic to aquatic life with long lasting effects.
  - H412 Harmful to aquatic life with long lasting effects.
  - EUH204 Contains isocyanates. May produce an allergic reaction.
- **Abbreviations and acronyms:**
  - SADT: Self Accelerating Decomposition Temperature
  - SAPT: Self Accelerating Polymerisation Temperature
  - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - IATA: International Air Transport Association
  - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - DNEL: Derived No-Effect Level (UK REACH)
  - PNEC: Predicted No-Effect Concentration (UK REACH)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - Flam. Liq. 2: Flammable liquids – Category 2
  - Org. Perox. C: Organic peroxides – Type C/D
  - Acute Tox. 4: Acute toxicity – Category 4
  - Skin Irrit. 2: Skin corrosion/irritation – Category 2
  - Skin Sens. 1: Skin sensitisation – Category 1
  - Skin Sens. 1B: Skin sensitisation – Category 1B
  - Repr. 2: Reproductive toxicity – Category 2
  - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
  - Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
  - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

(Contd. on page 12)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 03.08.2022

Version number 5 (replaces version 4)

Revision: 03.08.2022

**Trade name: Signum metal bond II**

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*  
· \* **Data compared to the previous version altered.**

(Contd. of page 11)

GB